

LSA GREASE L-EP3

THICKENER	NLGI	TEMP RANGE	BASE OIL VISCOSITY	EP	WATER RESISTANCE ON A SCALE OF 3
LITHIUM 12 HYDROXY STEARATE SOAP	3	0° C to +130° C	465 cSt @ 40° C	YES	2

LSA GREASE L-EP3 is outstanding multi-purpose extreme-pressure lithium hydroxy stearate grease with NLGI 3 consistency.

LSA GREASE L-EP3 is formulated with superior quality high viscosity base oils. Its components provide extreme pressure (EP) and anti-wear/anti-friction (AW) film protection under heavy loads maintaining lubrication and giving long service life. **LSA GREASE L-EP3** also provides a high level of oxidation, rust and corrosion protection.

APPLICATION

LSA GREASE L-EP3 is recommended for use in a wide range of automotive, industrial and general purpose mine applications and can be applied where a poly-lithium EP grease is specified. It is also suitable for wheel and rolling bearings, plain bearings, universal joints, chassis parts, gears, couplings.

Extends service life in heavy duty automotive trucks, buses, tractors and is a good general purpose Mine grease.

Because of its outstanding corrosion and water resistant properties it is suitable where water is present.

BENEFITS

- High viscosity base oils.
- Good resistance to water
- Excellent thermal and oxidation stability
- Stays in place in extreme environments
- Gives protection against rust and corrosion
- Excellent mechanical stability
- Extreme Pressure additives reduce wear under heavy loads
- Outstanding storage stability

TYPICAL CHARACTERISTICS

TEST	VALUE
COLOUR	GREEN
TEXTURE	Smooth Tacky
WORKED PENETRATION ASTM D-217	230
DROP POINT MINIMUM	190° C
TIMKEN OK LOAD, KG (ASTM D 2509)	23 KG
4-BALL WELD, KG	250 KG
4-BALL WEAR SCAR, MM	0.60 mm
ASTM WASH OUT % LOSS	10% MAX

Package Sizes

180 kg
20 kg
450 gm cartridges