

LSA PERFORMANCE SN 10W30

DESCRIPTION

LSA PERFORMANCE SN 10W30 is a premium SAE 10W/30 fuel efficient engine oil designed for the professional workshop and made using the latest synthetic technology base oils. It meets and exceeds the latest API SN and is suitable for most petrol engines under severe and varied operating conditions, such as high temperature motorway driving or low temperature stop-start driving.

LSA PERFORMANCE SN 10W30 is designed for vehicles that require a 10W30 engine oil meeting the strict ILSAC GF-5 fuel economy standard, as required by many late model engines.

Meets the following performance requirements:

- SAE Grade 10W/30
- API SN / SM
- ILSAC GF-5

Not suitable for Diesel engines.

Package sizes **1000 litre**
 205 litre
 20 litre

APPLICATION

LSA PERFORMANCE SN 10W30 is designed for use in modern multi-cam, multi-valve (including VVT) naturally aspirated, super charged & turbocharged engines including Hybrids. It is suitable for use in modern petrol, LPG and Hybrid vehicles including those running on Ethanol fuel blends, and in many late model European and Japanese engines where the ILSAC GF-5 fuel economy performance standard is specified.

It Can be used where previous API performance specifications (API SM, API SL and API SJ) were recommended, and where the earlier ILSAC GF-3 or GF-4 specifications were required

TYPICAL CHARACTERISTICS

| Properties | Unit | Value |
|--------------------|------|--------|
| SAE Grade | | 10W/30 |
| Viscosity @ 40°C | cSt | 68 |
| Viscosity @ 100°C | cSt | 10.5 |
| Viscosity Index | | 140 |
| Density @ 15°C | g/ml | 0.874 |
| Flash Point COC °C | | 205 |
| Pour Point °C | | -36 |