

LSA GREASE LXR 2

THICKENER	NLGI	TEMP RANGE	BASE OIL VISCOSITY	TACKINESS ADDITIVE	EP	WATER RESISTANCE ON A SCALE OF 3	SOLID LUBRICANT
LITHIUM COMPLEX	2	-20° C to 150° C	680 cSt @ 40° C	YES	YES	2	NO

GREASE LXR 2 is a premium heavy-duty grease for plain bearings operating under high load and high temperatures in mining, quarries and similar industries. Preferred for off-road parts such as ball joints and drive shafts.

GREASE LXR 2 is fortified with extreme pressure anti wear and anti-corrosion additives and compounded with tackiness agent to provide excellent sealing against ingress of dirt and moisture.

BENEFITS

- Excellent load bearing, See four-ball weld below.
- Compatible with other lithium and lithium complex greases.
- Very high viscosity base oil for high film strength.
- Corrosion resistance for wet conditions.
- Excellent mechanical stability under vibrating conditions.

TYPICAL CHARACTERISTICS

TEST	VALUE
COLOUR	DARK RED
SOAP TYPE	LITHIUM COMPLEX
WORKED PENETRATION	280
DROP POINT	260° C
FOUR BALL WELD, KG	320 KG

Package Sizes **180 kg** **20 kg** **450 gm**