## **Product**Data Sheet



### FARM OIL 15W40

A special Super Tractor Oil Universal (STOU) specifically formulated to service tractors with just one lubricant where formerly up to four or more oils where required.

It is recommended for diesel 4-stroke engines normally aspirated and turbocharged as well as gasoline engines, transmissions, differentials, final drives, hydraulic systems, wet brakes and power take-off clutches.

- ✓ Hydraulic performance and gear performance satisfies the requirements of off-highway construction, transport, mining, industrial and marine equipment.
- ✓ Suitable for manual gearboxes of cars, vans and light commercial vehicles where an API GL4 80W85 gear oil specification is required.

**ADVANTAGES** 

- Rationalization of grades and packages. Can replace 4 or more tractor lubricants.
- Good protection for gearboxes due to minimal foaming and stable lubricating film.
- For use in normally aspirated and turbocharged diesel engines and petrol engines using leaded or unleaded fuel.
- May be used for four stroke petrol engines in agricultural equipment.
- Effective lubrication when high load service conditions are experienced in transmissions, axles, engines and hydraulic systems.
- The balanced friction control ensures proper functioning of wet brake and PTO clutches and suppresses chatter without diminishing braking capacity.

FARM OIL 15W/40 is not recommended for hypoid differentials where an API GL-5 is recommended.

#### TYPICAL CHARACTERISTICS

Properties	Unit	Value
SAE Grade		15W/40
Viscosity @ 40°C	cSt	104
Viscosity @ 100°C	cSt	14.5
Viscosity Index		140
Density @ 15ºC	g/ml	0.88
Flash Point <sup>o</sup> C		220
Pour Point <sup>o</sup> C		-24
Sulphated Ash content	%	1.4
Total Base Number	mg KOH/g	10.9

**Pack Sizes** 

1000 litre 200 litre 20 litre

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.

Version: 7

1 of 2

Tel: +618 6254 7777

# **Product**Data Sheet



#### FARM OIL 15W40

Meets or recommended for the following requirements:

- STOU
- SAE 15W/40
- API CF-4/CG-4/SF
- API GL-4
- ACEA E2, E3
- ALISON C-4
- CATERPILLAR TO-2 (obsolete)
- FORD M2C 159B, C
- FORD M2C 86B, C
- JOHN DEERE J20, J27
- MAN 271
- Massey Ferguson M1139, M1144, M1145,M1135
- MB 227.1
- MIL L-2104D
- Ford New Holland 82009201, 2, 3
- Saucer Sunstand/Danfoss
- Sperry Vickers/ Eaton 1-280-S
- ZF TE-ML 06A, 06B, 06C, 07B

Version: 7 2 of 2

Tel: +618 6254 7777